



**DIMENSIONS APPEAR AS INCHES (mm).
TOLERANCES APPLY TO DIMENSIONS IN
INCHES**

ELECTRICAL SPECIFICATIONS:

FREQUENCY RANGE: 2 GHz - 18 GHz
 INSERTION LOSS: 1.2 dB TYP.
 1.5 dB MAX.
 VSWR: 1.5:1 TYP.
 1.8:1 MAX.
 DC VOLTAGE: 16 V MAX.
 DC CURRENT: 250 mA MAX.

ENVIRONMENTAL RATINGS

- TEMPERATURE: -40°C TO +85°C (OPERATING)
 -55°C TO +125°C (STORAGE)
 - HUMIDITY: MIL-STD-202G, METHOD 103B COND. B
 - SHOCK: MIL-STD-202G, METHOD 213B COND. B
 - VIBRATION: MIL-STD-202G, METHOD 204D COND. B
 - ALTITUDE: MIL-STD-202G, METHOD 105C COND. B
 - TEMP. SHOCK: MIL-STD-202G, METHOD 107G COND. A



NOTE: The above specifications are subject to change or revision. Specifications are at 25°C unless stated otherwise.

	QP microWAVE CÔLQUIDE 6 28231 LAS ROZAS MADRID, SPAIN	APPROVALS	DATE	SIGNED	DESCRIPTION: BIAS TEE 2 GHz - 18GHz	REV.:	SHEET:
		DRAW	06/02/13	AGM	CODE:	001	1 OF 1
		CHECKED	06/02/13	AGM	QP-BITEE-0218-02		
		APPROVED					