

2.92mm FEMALE

2.92mm FEMALE

Ø10,25 [0,40]

**QP<sub>mw</sub>**



P/N: QP-DCBLK-0040-04

S/N

36,00 [1,42]

**ALL DIMENSIONS SHOWN  
ARE IN mm [inch]**

**ELECTRICAL SPECIFICATIONS:**

FREQUENCY RANGE: 10 MHz - 40 GHz.  
 INSERTION LOSS: 1.5 dB MAX.  
 VSWR: 1.8:1 TYP.  
 2.0:1 MAX.  
 DC VOLTAGE: 16V MAX.  
 POWER HANDLING: +30dBm CW

**ENVIRONMENTAL RATINGS**

- TEMPERATURE: -40°C TO +85°C (OPERATING)  
 -55°C TO +125°C (STORAGE)  
 - HUMIDITY: MIL-STD-202G, METHOD 103B COND. B  
 - SHOCK: MIL-STD-202G, METHOD 213B COND. B  
 - VIBRATION: MIL-STD-202G, METHOD 204D COND. B  
 - ALTITUDE: MIL-STD-202G, METHOD 105C COND. B  
 - TEMP. SHOCK: MIL-STD-202G, METHOD 107G COND. A



NOTE: The above specifications are subject to change or revision. Specifications are at 25°C unless stated otherwise

<b>QP<sub>mw</sub></b>	<b>QP microWAVE</b> CÓLQUIDE 6 28231 LAS ROZAS MADRID, SPAIN	APPROVALS	DATE	SIGNED	DESCRIPTION: <b>DC BLOCK 10 MHz - 40 GHz</b>	REV.:	SHEET:
		DRAW	13/02/19	STO	<b>QP-DCBLK-0040-04</b>	001	1 OF 1
		CHECKED	13/02/19	BME			
		APPROVED	13/02/19	JAV			