



**ALL DIMENSIONS SHOWN
ARE IN mm [inch]**

ELECTRICAL SPECIFICATIONS:

FREQUENCY RANGE: 10 MHz - 40 GHz.
 INSERTION LOSS: 1.5 dB MAX.
 VSWR: 1.8:1 TYP.
 2.0:1 MAX.
 DC VOLTAGE: 16V MAX.
 POWER HANDLING: +30dBm CW

ENVIRONMENTAL RATINGS

- TEMPERATURE: -40°C TO +85°C (OPERATING)
 -55°C TO +125°C (STORAGE)
 - HUMIDITY: MIL-STD-202G, METHOD 103B COND. B
 - SHOCK: MIL-STD-202G, METHOD 213B COND. B
 - VIBRATION: MIL-STD-202G, METHOD 204D COND. B
 - ALTITUDE: MIL-STD-202G, METHOD 105C COND. B
 - TEMP. SHOCK: MIL-STD-202G, METHOD 107G COND. A



NOTE: The above specifications are subject to change or revision. Specifications are at 25°C unless stated otherwise

	QP microWAVE CÓLQUIDE 6 28231 LAS ROZAS MADRID, SPAIN	APPROVALS	DATE	SIGNED	DESCRIPTION: DC BLOCK 10 MHz - 40 GHz	REV.:	SHEET:
		DRAW	13/02/19	STO	CODE:	003	1 OF 1
		CHECKED	13/02/19	BME	QP-DCBLK-0040-05		
		APPROVED	13/02/19	JAV			