



**DIMENSIONS APPEAR IN mm.  
TOLERANCES APPLY TO DIMENSIONS IN mm.**

#### ELECTRICAL SPECIFICATIONS:

FREQUENCY RANGE:	10 MHz - 18 GHz
INSERTION LOSS:	1.2 dB TYP. 1.5 dB MAX.
VSWR:	1.5:1 TYP. 1.8:1 MAX.
DC VOLTAGE:	16 V MAX.
DC CURRENT:	250 mA MAX.

#### ENVIRONMENTAL RATINGS

- TEMPERATURE:	-40°C TO +85°C (OPERATING) -55°C TO +125°C (STORAGE)
- HUMIDITY:	MIL-STD-202G, METHOD 103B COND. B
- SHOCK:	MIL-STD-202G, METHOD 213B COND. B
- VIBRATION:	MIL-STD-202G, METHOD 204D COND. B
- ALTITUDE:	MIL-STD-202G, METHOD 105C COND. B
- TEMP. SHOCK:	MIL-STD-202G, METHOD 107G COND. A



NOTE: The above specifications are subject to change or revision. Specifications are at 25°C unless stated otherwise.



**QP microWAVE**  
CÓLQUIDE 6  
28231 LAS ROZAS  
MADRID, SPAIN

APPROVALS	DATE	SIGNED	DESCRIPTION:	REV.:	SHEET:
DRAW	15/09/20	BME	BIAS TEE 10 MHz - 18 GHz		
CHECKED	15/09/20	BME	<b>QP-BITEE-0018-02</b>	002	1 OF 1
APPROVED	15/09/20	JAV			