

SMA FEMALE

SMA MALE

10,25 [0,40]

41,70 [1,64]

**QP<sub>mw</sub>**



P/N: QP-DCBLK-0027-05  
S/N

**ALL DIMENSIONS SHOWN  
ARE IN mm [inch]**

**ELECTRICAL SPECIFICATIONS:**

FREQUENCY RANGE: 10 MHz - 27 GHz  
INSERTION LOSS: 1 dB TYP.  
1.5 dB MAX.  
VSWR: 1.2:1 TYP.  
1.5:1 MAX.  
DC VOLTAGE: 50 V  
POWER HANDLING: +30dBm CW

**ENVIRONMENTAL RATINGS**

- TEMPERATURE: -40°C TO +85°C (OPERATING)  
-55°C TO +125°C (STORAGE)  
- HUMIDITY: MIL-STD-202G, METHOD 103B COND. B  
- SHOCK: MIL-STD-202G, METHOD 213B COND. B  
- VIBRATION: MIL-STD-202G, METHOD 204D COND. B  
- ALTITUDE: MIL-STD-202G, METHOD 105C COND. B  
- TEMP. SHOCK: MIL-STD-202G, METHOD 107G COND. A



NOTE: The above specifications are subject to change or revision. Specifications are at 25°C unless stated otherwise

<b>QP<sub>mw</sub></b>	<b>QP microWAVE</b> CÓLQUIDE 6 28231 LAS ROZAS MADRID, SPAIN	APPROVALS	DATE	SIGNED	DESCRIPTION: <b>DC BLOCK 10 MHz - 27 GHz</b>	REV.:	SHEET:
		DRAW	13/02/19	STO	CODE:	003	1 OF 1
		CHECKED	13/02/19	BME	<b>QP-DCBLK-0027-05</b>		
		APPROVED	13/02/19	JAV			